



The UVS control provides maximum performance and efficiency for chip removal operations.

Add a UVS Ecologic Control for increased conveyor performance!



Systems equipped with a UVS Ecologic Control can save energy, decrease conveyor wear, and reduce coolant carryout.

OPTIONS

- OEM or field retrofit
- 8-pin I/O connection
- Common voltage options:
 - 0.5HP - 1.5HP, 110V 1Ø 50/60Hz (230V 3Ø Output)
 - 0.5HP - 25HP, 208/230V 3Ø 50/60Hz
 - 1HP - 50HP, 400/460V 3Ø 50/60Hz

DIMENSIONS

- 6.5" L x 6.5" W x 9.25" H

APPLICATIONS

The UVS Ecologic Control is applicable to almost any Jorgensen conveyor system.

BENEFITS

- Variable speeds:
 - Minimize conveyor wear
 - Save energy
 - Reduce coolant carryout
- Multiple power source options
- Ability to interface with the machine tool with optional I/O connection
- IP66-rated enclosure for indoor and outdoor use
- Easy operator interface
- Timer setting - on/off cycles to reduce coolant carryout
- Jam Manager® - automated program to clear minor jams for reduced machine downtime
- Load monitoring to protect conveyor components from torque spikes that could occur during a jam

**Jam Manager® function available on all power inputs and HP options*

Check out our website for a complete product list and more information.

Website: www.jorgensenconveyors.com
 Email: info@jorgensenconveyors.com
 Phone: 262-242-3089

